

# PIK♠ FÜLLER

2K HS 5:1 Acrylic primer

A two-component filling primer characterized by high filling properties and optimal fluidity. The product is highly resistant to damp patching, easy to process and defined by fast drying time. Does not clog abrasive papers. The product can be mixed with a solvent-based colorful top coating up to 5 % by volume.

The filling primer is suitable for various elements previously repaired with polyester putties . Applicable for manual and mechanical sanding, either in dry or wet systems.



PIK: 100%  
PIK Härter: 20%



1,8-2,5 mm



5-10 min  
20°C



1,8-2,5 mm



20°C: 6-7 h  
60°C: 45 min



wet sanding: P600-P1200  
dry sanding: P320-P400

Article no.	Capacity	Color
59045+59349	0,8L+0,16L hardener	white
59046+59349	0,8L+0,16L hardener	black
59047+59349	0,8L+0,16L hardener	grey
59293+59357	2,5L+0,5L hardener	white
59292+59357	2,5L+0,5L hardener	black
59048+59357	2,5L+0,5L hardener	grey
59049+59371	4L+0,8L hardener	white
59050+59371	4L+0,8L hardener	black
59051+59371	4L+0,8L hardener	grey

Amount of layers 2 - 3

The expiry date PIK Füller: 12 months  
PIK Härter: 6 months

*Our application advices, which we gave based on our experience, are given without any engagement from our side. The customer is requested to verify if the product meets his requirements. We cannot be held responsible for other results made by these tests. . Formula of this product according to directive 2004/42/EC.*