

PIK♠ FULL

Polyester filling putty

It is a fine-grained body filler characterized by high shaping properties regardless of the thickness of layers. Easy to process.

The optimal amount hardness and smooth non-porous surface allows to use this product as a filling and finishing putty. The filler putty is designed to even out the roughness of steel and fiberglass (polyester) surfaces.

Suitable for dry manual or machine sanding .In order to fill deeper scratches, several layers are needed.

The product is resistance to heating (up to 80°C).



The primed surfaces should be degreased, dry hand sanded (P220-P280) and degreased again.

In case of steel surface degrease, dry hand sand (P80-P120) and degrease again.

In case of aluminum, degrease, dull with abrasives and degrease again.

Old coating layers should be firstly degreased, dry sanded (P220-P280) and degreased again.



Pik Full: 100%
Hardener: 2-3%



Mix the ingredients thoroughly to achieve homogenous color



Applying time: 4-6 min



Apply with a putty knife



20°C: 20-25 min
60°C: 10 min

Article no.	Capacity	Color
59126	0,21kg	light yellow
59127	0,7kg	
59128	1,8kg	
59129	4,5kg	

Color light yellow

Caution Do not apply spray filler putty directly on reactive primers and other one-component acrylic or nitrocellulose products.

The expiry date **Pik Full: 12 months**

Our application advices, which we gave based on our experience, are given without any engagement from our side. The customer is requested to verify if the product meets his requirements. We cannot be held responsible for other results made by these tests. . Formula of this product according to directive 2004/42/EC.