

505

2K HS 5:1 Acrylic primer

High quality product designed for all kinds of surfaces. Provides high fluidity and thorough opacity of primed surface. It is characterizes by short hardening time even in case of applying thick layers and by good filling properties.

Suitable for sanding. The use of the product guarantees excellent top coating result.



505: 100%
TH-04: 20%
TVU: max. 25%



1,5-1,8 mm

Substrate	Adhesion low High
Metal	<div><div></div></div>
Steel, aluminium	<div><div></div></div>
Wood, concrete	<div><div></div></div>
Putties	<div><div></div></div>
Old coating layers	<div><div></div></div>



5-10 min
20°C



1,5-1,8 mm



~ 3 h
20°C



Machine sanding (dry):
P320-P500
Manual sanding (dry):
P280-P320
Machine sanding (wet):
P600-P1000
Manual sanding (wet):
P600-P800

Article no.	Capacity	Color
59341+59364		white
59342+59364	0,4+0,08L hardener	black
59343+59364		grey
59030+59017		white
59031+59017		black
59032+59017	0,8L+0,16L hardener	grey
59033+59017		graphite
59034+59017		yellow
59035+59017		red
59036+59432		white
59037+59432	2,5L+0,5L hardener	black
59038+59432		grey
59039+59018		white
59040+59018	4L+0,8L hardener	black
59041+59018		grey

Potlife	1 h
Amount of layers	2 - 3
Efficiency	5,5 m ² /l (layer thickness 100µm)
The expiry date	505: 24 months TH-04: 6 months

Our application advices, which we gave based on our experience, are given without any engagement from our side. The customer is requested to verify if the product meets his requirements. We cannot be held responsible for other results made by these tests. . Formula of this product according to directive 2004/42/EC.