

PIK♠SOFT

Polyester putty

It is a fine-grained body filler characterized by high shaping properties regardless of the thickness of layers. Easy to process.

The optimal amount of hardness allows to use this product as either filling or finishing putty. The filler putty is designed to even out the roughness of steel and fiberglass (polyester) surfaces.

Suitable for dry manual or machine sanding .In order to fill deeper scratches, several layers are needed.

The product is resistance to heating (up to 80°C).



Remove any traces of rust, old layers coatings and sand the surface.
Recommended grit of abrasives in case of various surfaces:
fiberglass: P60-P80; steel, wood: P80-P120;
old coating layers P220-P280.
After hardening, sand the surface with P80, P120 and P180 respectively.



Pik Soft: 100%
Hardener: 2-3%



Mix the ingredients thoroughly to achieve homogenous color



Applying time: 4-6 min



Apply with a putty knife



20°C: 20-25 min
60°C: 10 min

Article no.	Capacity	Color
59133	1,8kg	yellow
59134	4,5kg	
Color	yellow	
Caution	Do not apply spray filler putty directly on reactive primers and other one-component acrylic or nitrocellulose products.	
The expiry date	Pik Soft 12 months	

Our application advices, which we gave based on our experience, are given without any engagement from our side. The customer is requested to verify if the product meets his requirements. We cannot be held responsible for other results made by these tests. . Formula of this product according to directive 2004/42/EC.