

PP 1K

1K Plastic primer

The product is a one-component additive designed for priming various elements made of plastic. It is characterized with fast drying time.

Applicable in order to improve the adhesion to top layers (top coats, fillers) as well as to provide an insulating one.



Always remove all the impurities from plastic, pay special attention to disposing of any traces of products used to help to empty the essence from its package. They are available either in water or organic solvent washable forms. After cleaning, degrease the destined surface, then dull it, for example by using Scotch Brite type A fine hand pad. If necessary, heat the element up to 60°C for 60 minute, then degrease it again. The temperature in a spray booth as well as of the material should be about 18-25°C. Do not grind after drying. If necessary, dull the surface, for example by using Scotch Brite type A fine hand pad, in order to remove any impurities and roughness.



1,2-1,5 mm



5-10 min
20°C



1,2-1,5 mm



20°C : ~20 min



dry sanding: P360-P500
wet sanding: P600-P1000

Article no.	Capacity	Color
59071	0,4L	clear
59072	0,8L	

Caution

The product is unsuitable to be used on pure polyethylene PE, and pure Polypropylene PP in any car repairs shops.

The expiry date

PP 1K: 12 months

Our application advices, which we gave based on our experience, are given without any engagement from our side. The customer is requested to verify if the product meets his requirements. We cannot be held responsible for other results made by these tests. Formula of this product according to directive 2004/42/EC.