

Acryl Spray

1K acrylic coat spray

It is a fast-drying coat characterized by high coating properties as well as good adhesion to various substrates made of metal, plastic and wood.

The product is strongly resistant to negative weather conditions, chemical agents, petrol and ultraviolet radiation.



It can be applied on either processed or unprocessed substrates made of wood, metal, aluminum, stone or any kinds of plastic. Clean, dry and degrease the chosen surface beforehand. Remove any traces of old coating layers and rust. Then sand the surface. In case of plastic, heat the chosen element up to 50°C in order to remove any silicone remains.



Shake for 2 min and test spray on a carton.



Hold within 25-30 cm from a chosen surface



5-10 min



Hold within 25-30 cm from a chosen surface



Drying time in 20°C, 65 R.H.:
Touch dry: 5-10 min
Does not cohere: 20-30 min
Complete hardening: 24 h

Article no.	Capacity	Color/type
59092		white
59095	0,4L	black matt
59096		black

Scratch resistance

Difficulty level of polishing

Efficiency 1,25-1,75m²

Caution
After work clean the outlet of the aerosol - hold the can so the outlet is pointing down, press the button for 5 seconds to release the remaining content. The product is resistant to high temperature (up to 110°C)

The expiry date 12 months

Our application advices, which we gave based on our experience, are given without any engagement from our side. The customer is requested to verify if the product meets his requirements. We cannot be held responsible for other results made by these tests. Formula of this product according to directive 2004/42/EC.