

PIK♠KS

UBS Underbody protection

It is an underbody protection product which can be applied under any kind of top coatings. Provides long-lasting protection for car body in such places as sills, trunks, doors, spoilers both internally and externally, against corrosion and mechanical damage.

The product is elastic and characterized by high vibration insulation as well as adhesion to various surfaces such as polyester laminates, plastic or puttied, filled and coated substrates.



Remove any traces of rust, degrease and dull (PP120 – P150) the chosen surface beforehand. To achieve perfect results, the element should be treated with anticorrosive fillers. Cover the unprocessed surfaces. The original package is equipped with external threading suitable for a UBS spray gun. Shake the can to mix the product thoroughly directly before use. Apply with a UBS spray gun (pistol douching) in temperature 15-30°C. The applied layer must dry properly in order to over paint it with protective layers of top coat.



Shake before using.



4mm
(ok. 100µm)



Approximated
distance of application
is 25-30 cm



5-10 min



4mm
(ok. 100µm)



Approximated
distance of application
is 25-30 cm



20°C: 40-60 min

Article no.	Capacity	Color
59056		white
59057	1L	black
59058		grey
59220		white
59093	500ml	black
59094		grey

Caution

Clean the spray nozzle thoroughly after use! – Hold the can with the valve pointing downward, press the button for about 5 seconds to empty the can of any remaining contents.

The expiry date PIK KS: 12 months

Our application advices, which we gave based on our experience, are given without any engagement from our side. The customer is requested to verify if the product meets his requirements. We cannot be held responsible for other results made by these tests. . Formula of this product according to directive 2004/42/EC.