

KP

Underbody protection

The product is destined for long-lasting protection of the car underbody against corrosion. Applicable with an underbody coating spray gun.

The agent is based on bitumen and wax and is characterized by perfect soundproofing properties. After drying, the surface is strongly adherent and creates a protective barrier against negative weather conditions or gravel.



Clean, dry, dust, degrease and remove any traces of rust from the chosen surface. Clean, dry, dust, degrease and remove any traces of rust from the chosen surface.



Shake before using.



Apply with an underbody coating spray gun with air pressure of 3-6 bar. Optimal distance during applying is 30 cm. In order to achieve thinner layer, let the previous ones dry before continuing. It can be applied without creating any cobwebs, dusting or dripping.



Drying time in 20°C, 65 R.H.:

Touch dry: 120-180min.
(600µm wet layer)
Complete hardening: 4-6h
(600µm wet layer)

Article no.	Capacity	Applying
59059	1kg	brush
59060	1L	spray gun
59097	500ml	spray

Caution Clean the surface and used tools properly with a solvent.

The expiry date 24 months

Our application advices, which we gave based on our experience, are given without any engagement from our side. The customer is requested to verify if the product meets his requirements. We cannot be held responsible for other results made by these tests. Formula of this product according to directive 2004/42/EC.