

1K Klarlack

Clear coat spray

It is a fast-drying one-component clear coat spray characterized by high gloss and adhesion to various kinds of substrates. It provides long-lasting protection against corrosion, scratches and other impacts. The product is resistant to chemical agents, petrol and negative weather conditions.



Remove any traces of old coating layers and rust. Then sand the surface. In case of plastic, heat the chosen element up to 50°C in order to remove any silicone remains.



Shake for 2 min and test spray on a carton.



Hold within 25-30 cm from a chosen surface



5-10 min



Hold within 25-30 cm from a chosen surface



Drying time in 20°C, 65 R.H.:
Touch dry: 5-10 min
Does not cohere: 20-30 min
Complete hardening: 24 h

Article no.	Capacity	Type
59098	0,4L	Gloss

Gloss



Scratch resistance



Difficulty level of polishing



Efficiency

1,25-1,75m²

Caution

After work clean the outlet of the aerosol - hold the can so the outlet is pointing down, press the button for 5 seconds to release the remaining content. The product is resistant to high temperature (up to 110°C)

The expiry date

12 months

Our application advices, which we gave based on our experience, are given without any engagement from our side. The customer is requested to verify if the product meets his requirements. We cannot be held responsible for other results made by these tests. . Formula of this product according to directive 2004/42/EC.