

# 1K Silver

acrylic coat

It is a fast-drying coat perfect for rims, hubcaps and other small underbody elements and decorations. It is characterized by high adhesion to various surfaces, good resistance to scratches, petrol and other chemical substances as well as to UV radiation. It provides protection against corrosion, salt and water.

Do not cover by a clear coat.



It can be applied on either processed or unprocessed substrates made of wood, metal, aluminum, stone or any kinds of plastic. Clean, dry and degrease the chosen surface beforehand. Remove any traces of old coating layers and rust. Then sand the surface. In case of plastic, heat the chosen element up to 50°C in order to remove any silicone remains.



Shake for 2 min and test spray on a carton.



Hold within 25-30 cm from a chosen surface



5-10 min



Hold within 25-30 cm from a chosen surface



Drying time in 20°C, 65 R.H.:  
Touch dry: 5-10 min  
Does not cohere: 20-30 min  
Complete hardening: 24 h

Article no.	Capacity	Color
59103	0,4L	silver

Efficiency 1,25-1,75m²

Caution

After work clean the outlet of the aerosol - hold the can so the outlet is pointing down, press the button for 5 seconds to release the remaining content. The product is resistant to high temperature (up to 110°C)

The expiry date 12 months

*Our application advices, which we gave based on our experience, are given without any engagement from our side. The customer is requested to verify if the product meets his requirements. We cannot be held responsible for other results made by these tests. Formula of this product according to directive 2004/42/EC.*