

PIK♠ LIGHT

Polyester putty

Super lightweight polyester putty, has very good adhesion to substrates of steel, aluminum, galvanized steel, wood and polyester laminates.

Soft and easy to handle, lighter by 45% from the universal filler putty. Especially recommended to repair large areas, eg. The roof, doors, trunk lid, the body of passenger cars and trucks, buses and rail vehicles.



Remove any traces of rust, old layers coatings and sand the surface.
Recommended grit of abrasives in case of various surfaces:
fiberglass: P60-P80; steel, wood: P80-P120;
old coating layers P220-P280.
After hardening, sand the surface with P80,
P120 and P180 respectively.



Pik Light: 100g
Hardener: 2-3g



Mix the ingredients thoroughly to
achieve homogenous color



Applying time: 3-5 min



Apply with a putty knife



20°C: 16-30 min



dry sanding and machine
sanding: **P150-P320**

Article no.	Capacity	Color
59118	1L	beige

Color beige

Caution An overdose of the hardener may
lead to topcoat discoloration.
Application of the product below
15°C is not recommended.

The expiry date **Pik Light: 12 months**

*Our application advices, which we gave based on our experience, are given without any engagement from our side. The customer is requested to verify if the product meets his requirements. We cannot be held responsible for other results made by these tests. .
Formula of this product according to directive 2004/42/EC.*