

611

Spray filler putty

The 611 product is destined for spray gun application. It creates perfectly smooth coating, regardless of the size of the surface. It is characterized by great insulating properties in case of primers, acrylic coats and polyester putties. Provides high protection against various defects on the surfaces which can be caused by not following the recommended amount of hardener, either too low or too high, during applying putties with putty knife. It creates layers of good adhesion and may be also applied on vertical elements.



After hardening, sand the surface: rough sanding - P180-P240; finishing sanding - P240-P320
After sanding, cover the spray filler putty with an acrylic primer.



611: 100%
Hardener: 3-4%
Thinner: max 10%



2,2-3,0 mm



5 min



2,2-3,0 mm



20°C: 2-3 h
60°C: 30 min

Article no.	Capacity	Color
59116	1kg	light grey
59369	3kg	
Potlife	20-30 min	
Color	light grey	
Caution	Do not apply the putty directly on a reactive primer or any other one-component acrylic and nitrocellulose products.	
Caution	After hardening, sand the surface: rough sanding - P180-P240; finishing sanding - P240-P320 After sanding, cover the spray filler putty with an acrylic primer.	
The expiry date	611: 12 months	

Our application advices, which we gave based on our experience, are given without any engagement from our side. The customer is requested to verify if the product meets his requirements. We cannot be held responsible for other results made by these tests. . Formula of this product according to directive 2004/42/EC.