

HT300

2K LS 2:1 Clear coat

The HT300 clear coat is highly recommended in cases when short period of drying is needed. The product should not be used in high temperature and especially not for whole car body painting. It provides a high glossed surface and is strongly resistant to any mechanical impacts as well as other chemicals and atmospheric agents.

The product does not required using any thinners.



Before applying, clean the surface with silicone remover and let it evaporate. Grind with suitable abrasive paper. Grind recommended for original layer: P800-P1000 in "wet on wet" system, and P600-800 in dry system. Clean using silicone remover. Always clean and dust the chosen surface with an antistatic cloth.



HT300: 100%
TH-07: 50%



1,3-1,5 mm



5-7 min
20°C



1,3-1,5 mm



4-5 h/20°C

Article no.	Capacity	Package
59344+59372	0,5L+0,25L hardener	6
59345+59379	1L+0,5L hardener	6
59346+59380	5L+2,5L hardener	4

Recommended hardener: TH-07

Gloss

Paint spreading

Scratch resistance

Difficulty level of polishing

Potlife 1-1,5 h

The expiry date HT300: 12 months
TH-07: 6 months

Our application advices, which we gave based on our experience, are given without any engagement from our side. The customer is requested to verify if the product meets his requirements. We cannot be held responsible for other results made by these tests. . Formula of this product according to directive 2004/42/EC.