

F17

FLASH Acrylic Primer 2K 4:1 HS

F17 Flash from eXpert Line is a perfect acrylic filling primer, manufactured in HS hardness scale (High-Solid), which can be grinded after application in less than 1 hour (in room temperature).

The product shows anticorrosive properties, what ensures durability of the coating. The product can be applied to many types of surfaces, such as: old paint coatings, epoxy and reactive primers, directly on steel, galvanized steel, aluminum or fiberglass material.

F17 can be applied by "wet on wet" method.



Always clean the surface with silicone remover before application. Grind with suggested granulation of abrasive paper.



F17: 100%
F17H: 25%
TVU: do 20%



1,2-1,9 mm



5 min
20°C



1,2-1,9 mm



20°C: 1 h



wet sanding: **P600-P800**
dry sanding: **P320-P400**

Article no.	Capacity	Color
59598 + 59599	1L+0,25L hardener	grey

Substrate	low	Adhesion	High
Metal	<div><div></div></div>		
Steel, aluminium	<div><div></div></div>		
Putties	<div><div></div></div>		
Old coating layers	<div><div></div></div>		
Potlife	1 h		
Amount of layers	1-2		
Viscosity	25-65 s DIN Cup 4mm		
The expiry date	F17: 12 months F17: 9 months		

Our application advices, which we gave based on our experience, are given without any engagement from our side. The customer is requested to verify if the product meets his requirements. We cannot be held responsible for other results made by these tests. Formula of this product according to directive 2004/42/EC.