

777

2K VHS 2:1 Clear coat

T777 2K 2:1 special acrylic Clearcoat from eXpert line series has a mayor quantity of high solids and low contents of the volatile organic compounds (VOC) – used in cases where the highest quality of the coating is required.

It is characterized by a very good flow, very high gloss and high hardness after curing; At the same time, it retains flexibility. It is resistant to scratches, weather conditions and UV-rays.



1st step: Before applying, clean the surface with silicone remover and let it evaporate.

2nd step: Grind with a suitable abrasive paper. Grind recommended for the original layer: P800-P1000 in "wet on wet" system, and P600-800 in dry system.

3rd step: Clean using silicone remover.

4th step: Always clean and dust the chosen surface with an antistatic cloth.



777: 100%
777H: 50%
TVU: 30-35%



1,3-1,4 mm



3-5 min
20°C



1,3-1,4 mm



12 h/20°C
30 min/60°C

Article no.	Capacity	Package
59608 + 59609	1L+0,5L hardener	6

Recommended hardener: 777

The product should be mixed with TVU

Gloss

Paint spreading

Scratch resistance

Difficulty level of polishing

Viscosity 15-17 s DIN Cup 4mm

Potlife 4-6 h

The expiry date **777:** 18 months
777H: 6 months

Our application advices, which we gave based on our experience, are given without any engagement from our side. The customer is requested to verify if the product meets his requirements. We cannot be held responsible for other results made by these tests. . Formula of this product according to directive 2004/42/EC.