

TP100

ONE STEP SEALER Insulating Primer 2K 4:1

TP100 ONE STEP SEALER is a transparent, two-component insulating primer with anti-corrosive properties, which gives adhesion on old paints and can be applied by wet-on-wet method, eliminating the need for substrate grinding. Its use does not require surface mating – only for surfaces with very high gloss it is necessary to matt.

Very useful in cases where there is a need to refresh the old coating, or to perform a quick repair on the old paint.

Ideal for use before application of topcoats when painting the whole car. Suitable for tinting, by adding max. 5% of acrylic paint.



Aged, but stable coating surfaces clean and degrease by using silicon remover. Places that are potentially exposed to mechanical damage grind with grey Scotch Brite to increase adhesion. If it is not being coated in next 24 hours, matt it and apply covering lacquer.



TP100: 100%
TPH100: 25%
Thinner: max 30%



1,6-1,9 mm



2-5 min
20°C



20°C: 5 min
(wet on wet method)

Article no.	Capacity
59613+59614	0.8L + 0,2L hardener
Substrate	low Adhesion High
Steel	
Old paint surface	
Non-ferrous metal	
Potlife	1 h
Amount of layers	1-2
Viscosity	15-17 s DIN Cup 4mm
The expiry date	TP100: 12 months TPH100: 9 months

Our application advices, which we gave based on our experience, are given without any engagement from our side. The customer is requested to verify if the product meets his requirements. We cannot be held responsible for other results made by these tests. . Formula of this product according to directive 2004/42/EC.